



Technological Arts Inc.

Technological Arts

NanoCore12C32S Module, RS232 Interface, 24-pin

USD \$49.00



Product Info

NanoCore12™ is a low-cost platform that brings the advanced features of the 9S12C microcontroller family within easy reach of engineers, students, and hobbyists. The flexible design accommodates all facets of training, evaluation, development, and application prototyping.

While there are several DIP-format MCU modules on the market, none of them comes close to the power and value of NanoCore12! Others are based on RISC processors-- some relying on serial program memory, and have limited or no hardware subsystems on-chip. NanoCore12 is the only complete family of DIP modules based on a high-speed CISC device. Since RISC processors only possess primitive instructions, their high speed is necessary, in order to produce acceptable computing power. With a CISC processor running at the same speed, the overall performance is vastly improved-- and performance improvement is in orders of magnitude for certain types of operations. The HCS12 instruction set includes powerful DSP-like instructions, 16-bit arithmetic, and the architecture implements memory-to-memory moves, and many powerful addressing modes. These features are way beyond what most PIC, AVR, and 8051 processors offer today.

Module Features:

- based on the 9S12C32 MCU (48-pin LQFP version)
- includes 8 Mhz crystal
- 24 MHz bus speed (via PLL)
- local 5 Volt low-dropout 100 mA regulator
- includes RS232 transceiver circuit

- has on-chip Serial Monitor
- supports standalone operation
- 32K Bytes Flash
- 2K Bytes Ram
- 24-pin DIP form-factor
- **low-cost gold-plated 0.020" square pins**
- pinout virtually identical to BASICStamp2^{Â®}

- this product ships with hardcopy data sheet and schematic diagram
- data sheets, manuals, and all other resources for this product can be found at www.NanoCore12.com

Â®BASICStamp is a registered trademark of Parallax Inc.

Product Details

- supports programming in C, BASIC, Forth, assembler, etc.
- no special Flash programming voltage or switch required
- fast in-circuit programming
- small footprint on-chip bootloader/monitor and free uBug12 GUI for quick loading/debugging of user programs on Windows, Linux, and Mac platforms
- Run/Load switch for choice of Standalone or Monitor operation following reset
- compatible with virtually all 9S12 development tools on the market
- compatible with CodeWarrior

Flash-based code development using on-chip debug/monitor With a 2K Flash-resident debug/monitor program, you'll be able to load your program into the remaining 30K Flash via the serial port using CodeWarrior or uBug12. The entire 30K Flash can be programmed in about 3 seconds! To use the monitor for debugging or code-loading, just set the switch to LOAD. To run your standalone program thereafter, leave the switch at RUN.Â A program you load into Flash this way will run every time you apply power or reset the board in Run Mode.

Flash-based code development using a BDM pod If you want to take advantage of a more advanced development tool (such as USBDMILT), the entire 32K Flash can be used, because the Flash-resident bootloader is no longer needed.

- implements PLL loop filter circuit, supporting up to 48MHz operation (24 MHz bus speed)
- capable of 3-Volt operation
- standard 6-pin BDM connector for full debugging capabilities (with an optional BDM pod)
- ECLK signal is user-accessible (via pad on circuit board)

- access to eight 10-bit analog input or digital I/O port lines (Port AD)
- access to eight digital I/O port lines (Port T)
- up to five PWM timer channels (PT0 - PT4)
- up to eight Input Capture/Output Compare pins (Port T)
- internal programmable pullup and pulldown resistors on most pins
- user access to MCU reset signal
- sturdy gold-plated square pins plug into standard dual-leaf DIP sockets or solderless breadboard

Â®BASICStamp is a registered trademark of Parallax Inc.

[Vendor Information](#)